

PS polystyrene sale

Variant	Price	Details
multicoloured	790	
black	840	refer to Spec.sheet 1
black, impact-resistant	880	refer to Spec.sheet 2
pearl white	910	

All prices in Euro / tonne, ex Zevenbergen - excluding 19% VAT.

Grinding and granulating on contract base

Packing - octabins or Big bags
- in bulk feed silos

Transport - in trucks
- in bulk carriers

Payment by mutual agreement

Spec.sheet 1 PSHI black regranulate

Meltflowindex 200 °C 5 kg	7-9	g/10 min.	ASTM D 1238-90b
Vicat B	97	°C	ASTM D 1525-91
Tensile strength 5 (mm/min)	20,5	N/mm ²	ASTM D 638m91
Elongation on breaking	37,3	%	ASTM D 638m91
Izod impact test	6,6	kJ/m ²	ISO 180

Spec.sheet 2 PSHI black, impact-resistant regranulate

Meltflowindex 200 °C 5 kg	7-9	g/10 min.	ASTM D 1238-90b
Vicat B	97	°C	ASTM D 1525-91
Tensile strength 5 (mm/min)	20,5	N/mm ²	ASTM D 638m91
Elongation on breaking	37,3	%	ASTM D 638m91
Izod impact test	8,0	kJ/m ²	ISO 180